



Tech Info Library

A/UX: Daemons Needed for NFS (9/94)

Article Created: 12 October 1990

Article Reviewed/Updated: 6 September 1994

TOPIC -----

What daemons need to be running for NFS?

DISCUSSION -----

By using the "ps" command, you can determine if all the NFS daemons necessary for an NFS server are running.

- 1) Log on to the system as "root".
- 2) Enter the line: ps -ef
- 3) If all the necessary daemons are running, you should find these lines within the output:

```
root  98      1 0 09:42:27?      0:00 /etc/portmap
root  100     100 0 09:42:28?      0:00 /etc/nfsd 4
root  102     100 0 09:42:29?      0:00 /etc/nfsd 4
root  103     100 0 09:42:29?      0:00 /etc/nfsd 4
root  104     100 0 09:42:29?      0:00 /etc/nfsd 4
root  116      1 0 09:42:37?      0:00 /etc/inetd
```

The above lines may not appear together, and the numbers in the columns may differ on your system.

If you don't have the nfsd 4 lines appear, you may try the following procedure to start the /etc/biod daemon.

- 1) Log on as "root".
- 2) Edit the file /etc/inittab
- 3) Enter these changes:

- Change this line: nfs4:2:off:/etc/biod 4

- To this line: nfs4:2:wait:/etc/biod 4
 - Change this line: nfs8:2:off:/etc/mount -at nfs > /dev/syscon 2>&1
 - To this line: nfs8:2:once:/etc/mount -at nfs > /dev/syscon 2>&1
- 4) Now, when your system is booted into multi-user mode, the daemon will automatically be started.

Article Change History:

- 06 Sep 1994 - Reviewed.
- 31 Aug 1994 - Reviewed.

Support Information Services
Copyright 1990-94 Apple Computer, Inc.

Keywords: <None>

=====

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 6276