



Tech Info Library

A/UX: How to Mount a Remote NFS System Automatically (9/94)

Article Created: 12 October 1992

Article Reviewed/Updated: 6 September 1994

TOPIC -----

How do I make a remote NFS file system mount automatically at startup?

DISCUSSION -----

- 1) Log on the system as "root".
- 2) First, remember that you will need a directory on which you will mount the remote file partition. Let's call the directory "mntdir".
- 3) Create the directory mntdir in "/"; enter the command-line:
mkdir /mntdir
- 4) You need the name of the remote file partition. Use the /usr/catman directory on the remote system "my_system_name" as an example.
- 5) Edit the file /etc/fstab. This file contains a list of file partitions that will automatically be mounted at boot time.
- 6) Add the line: my_system_name:/usr/catman /mntdir nfs rw,soft 0 0
- 7) Save the file and exit the editor.
- 8) Shut the system down.
- 9) Bring the system back up into multi-user mode.
- 10) The names of the local and remote partitions will be listed as they are automatically mounted.

Article Change History:

06 Sep 1994 - Reviewed.

31 Aug 1992 - REVIEWED for technical accuracy

Support Information Services

Copyright 1990-94 Apple Computer, Inc.

Keywords: <None>

=====

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 6273