



Tech Info Library

A/UX: How to Adjust the Kernel Parameter NUBUFS

Article Created: 29 October 1990

Article Change History

08/31/92 - REVIEWED

- For technical accuracy.

TOPIC -----

I want to connect to Ethernet. The figures for a 5MB configuration were typed in. Running the command

```
netstat -r
```

brings up the message

```
mexpand returning 0
```

DISCUSSION -----

A request to allocate memory to use for memory buffer space was denied. Wait a short while, and see if the condition clears up before rebooting. You may also consider increasing the size of the buffers available; adjust the kernel parameter NUBUFS. To do this, follow these steps:

- 1) Log in as "root" and bring the system down into single-user mode.
- 2) Execute "kconfig -av | grep NMBUFS". It should return the network memory buffers configured in the kernel. A/UX is distributed with NMBUFS=500.
- 3) Type "kconfig -n /unix"
- 4) Type "NMBUFS=" followed by the number you would like to increase it to followed by a carriage return. Try increasing the number of mbufs to 1000; type "NMBUFS=1000"
- 5) Type a Ctrl-D to exit kconfig. The shell prompt will reappear.
- 6) Execute "sync; sync; sync; reboot". The system will sync and reboot

itself. Bring it back up.
Copyright 1990 Apple Computer, Inc.

Keywords: <None>

=====

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 6478