



# Tech Info Library

## A/UX: Making Apple DoubleFormat the Default File Format (6/94)

Article Created: 30 November 1992

Article Reviewed/Updated: 23 June 1994

TOPIC -----

How can I set the A/UX Finder to AppleDouble Format?

DISCUSSION -----

Under A/UX, you can change the default file-creation format to AppleDouble Format (instead of AppleSingle Format). The steps below describe how to override the default, so that A/UX creates files in AppleDouble file format:

- 1) Change the kernel Toolbox TBFILEFORMAT environment variable from 0 (for AppleSingle Format) to 1, as appropriate to your login shell:

If the login shell is the Bourne Shell (sh) or the Korn Shell (ksh), insert the following lines into the user's .profile file:

```
TBFILEFORMAT=1
export TBFILEFORMAT
```

If the login shell is the C Shell (csh), insert the following line in the user's login file (NOT in .cshrc):

```
setenv TBFILEFORMAT 1
```

- 2) Log out and log in again to activate the change.
- 3) On the Apple Workgroup Server 95 you can edit the file /mac/bin/mac32 in order to make Apple Double Format the default format.

Important: After making this change, all Macintosh applications files created will be in AppleDouble format. You can, however, use the "fcnvt" utility to convert such files to any desired format.

Article Change History:

23 Jun 1994 - Included AWS 95 to article.

Support Information Services

Copyright 1992-94, Apple Computer, Inc.

Keywords: supt

=====  
This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 11061