



# Tech Info Library

## Super Serial Card: Cable for US Robotics Password Modem (11/96)

Article Created: 07 November 1985

Article Reviewed/Updated: 21 November 1996

TOPIC -----

Listed below are the cable pinouts for connecting the Super Serial card to a US Robotics Password Modem.

DISCUSSION -----

Super Serial Card (SSC)	Pin	Cable	Pin	Modem Connector
Frame Ground .....	(FG).....		1	
Transmit Data	(Tx) .....	<----->	2	
Receive Data	(Rx) .....	<----->	3	
Request to send	(RTS) ....		4	
Clear To Send	(CTS) ....		5	
Data Set Ready	(DSR) ....		6	
Signal Ground .....	(SG).....	<----->	7	
Data Carrier Detect	(DCD) ....		8	
Secondary Clear To Send	(SCTS) ...		19	
Data Terminal Ready	(DTR) ....	<----->	20	

### Super Serial Card dip switch settings

- SW1: all up except 1 (down)
- SW2: all up except 6,7 (down)

\* Set Super Serial Card configuration block to Terminal.

### Modem dip switches settings

\* Dip switch settings for Modem: ALL DOWN

### Article Change History:

21 Nov 1996 - Reviewed for technical accuracy, revised formatting.

Copyright 1985-96, Apple Computer, Inc.

Keywords: <None>

=====

This information is from the Apple Technical Information Library.

19961122 07:37:55.00

Tech Info Library Article Number: 1465