



Tech Info Library

Apple IIc Plus: Specifications (Discontinued 11/90)

This article last reviewed: 13 September 1988

Here are specifications for the Apple IIc Plus:

CENTRAL PROCESSING UNIT (CPU)

- Microprocessor: 4 Mhz 65C02
- Clock Speed: 1 or 4 Mhz (user selectable -- press ESC key when you power the unit on)
- Address bus: 16 bits
- Address range: 65,536 bytes (64K)
- Data bus: 8 bits
- Registers (8 bit): accumulator, two index registers, stack pointer, and processor status register

MEMORY

- 128K of RAM (random-access memory), optionally expandable to 1.125 megabytes
- 32K of ROM (read-only memory), containing:
 - System monitor
 - AppleSoft BASIC interpreter
 - 80-column display firmware

TEXT DISPLAY MODES

- 80-column text (80 columns by 24 lines)
- 40-column text (40 columns by 24 lines)
- All text can appear on the screen as normal, inverse, flashing, or MouseText characters

GRAPHICS DISPLAY MODES

- Double high-resolution (560 dots horizontally by 192 dots vertically; 16 colors)
- High-resolution (280 dots horizontally by 192 dots vertically; 6 colors)
- Low-resolution (40 dots horizontally by 48 dots vertically; 16 colors)
- All graphics can be configured to allow four lines of text at the bottom of the screen.

KEYBOARD

- 63-key full-sized keyboard
- Full 128-character ASCII, including 96 uppercase and lowercase alphanumeric characters, and 32 control characters
- Special-purpose keys: shift, caps lock, control, escape, return, tab, delete, up arrow, down arrow, left arrow, right arrow, reset, open apple, option
- Keyboard is switchable between QWERTY and Dvorak layouts

- Includes volume slide control for speaker

DISK DRIVE

- Disk size: 3.5 inches
- Capacity: 800 kilobytes
- Recording surfaces: 2
- Tracks per surface: 80
- Blocks per disk: 1,600
- Push button for motorized eject

INTERFACES

- External disk drive port using 19-pin, D-style connector, allows a daisy-chain connection of up to three additional drives (Apple 3.5 Drive, UniDisk 3.5, and/or Apple 5.25)
- Two RS-232 serial ports with 8-pin minicircular connectors (for printer, modem, and other accessories)
- NTSC (composite) color video, via RCA phone jack
- 15-pin, D-style connector for video expansion
- 9-pin, D-style connector for mouse, joystick, hand controllers, or other accessories
- Internal, 34-pin connector for memory expansion up to 1.125 megabytes
- Standard, 3-pin grounded power plug

ELECTRICAL REQUIREMENTS

- Line voltage: 90 to 130 volts AC
- Line frequency: 50 to 60 hertz
- Maximum power consumption: 20 watts continuous
- Supply voltages:
 - +5 volts (+-5%)
 - +12 volts (+-10%)
 - 12 volts (+-10%)
- Maximum supply currents:
 - +5 volts=1.5 amps
 - 5 volts= 30 milliamps
 - +12 volts= 0.9 amps continuous -- 1.5 amps intermittent
 - 12 volts= 100 milliamps

ENVIRONMENTAL REQUIREMENTS

- Operating temperature: 50 to 104 degrees F (10 TO 40 degrees C)
- Relative humidity: 20% to 95%

SAFETY AND EMI QUALIFICATIONS

- FCC part 15 Class B Computing Devices
- UL 11 Office Appliances and Business Equipment

SIZE AND WEIGHT

- Height: 2.5 inches (6.35 cm)
- Width: 12 inches (30.48 cm)
- Depth: 11.5 inches (29.2 cm)
- Weight: 7lb. (3.2 kg)

Included with the Apple IIc Plus package:

- Apple IIc Plus personal computer with built-in 800K disk drive
 - Power cord
 - Apple II System Disk
 - Tutorial disk
 - Owner's guide
 - Apple II System Disk User's Guide
 - A Touch of AppleSoft BASIC manual
 - Limited warranty statement
 - Packing list
- Copyright 1988 Apple Computer, Inc.

Keywords: SPECSHT

=====

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 3247