



Tech Info Library

Apple II Monochrome Monitors: Specifications (Discontinued)

Article Created: 31 May 1991

TOPIC -----

This article describes two Apple II Monochrome Monitors:

- the Apple Monochrome Monitor (for the Apple IIGS, Apple IIc Plus, or Apple IIc)
- the Apple Monochrome Monitor IIe (for the Apple IIe, Apple II Plus, or Apple II)

DISCUSSION -----

Both these monitors display crisp, easy-to-read text and sharp graphics. Their 12 inch high-resolution antiglare screens are easy on your eyes, making them the low-cost displays of choice for text-based applications and other applications that don't require color.

System Requirements

- To use an Apple Monochrome Monitor IIe, you need an Apple IIe, Apple II Plus, or Apple II personal computer.
- To use an Apple Monochrome monitor, you need an Apple IIGS, Apple IIc Plus, or Apple IIc personal computer. If you have an Apple IIc Plus or Apple IIc, you may also wish to purchase an Apple Monitor Stand.

Picture Tube

- Apple Monochrome Monitor IIe
12 inches (30.5 centimeters) diagonal
High-contrast
Antiglare
90 degrees diagonal deflection
Green Phosphor (EIA Type P31)
- Apple Monochrome Monitor
12 inches (30.5 centimeters) diagonal
High-contrast
Antiglare
90 degrees diagonal deflection

White Phosphor (EIA Type P4)

Active Display Area

- both monitors:
215mm horizontal by 160mm vertical (remainder of area is used for border)

Scanning

- both monitors:
EIA standard: 525 lines; 30 frames, 60 fields/second; overscan

Scan Rates

- both monitors:
Horizontal: 15.7 kilohertz
Vertical: 59.9 hertz

Input Signal

- both monitors:
Composite video, 1.0 (± 0.1) volts peak-to-peak, negative sync

Video Bandwidth

- both monitors:
Less than 3 decibels down at 10 megahertz

Display Capability

- Apple Monochrome Monitor IIe
With Apple IIe: 560 dots horizontally by 192 dots vertically
- Apple Monochrome Monitor
With Apple IIc Plus or Apple IIc: 560 dots horiz. by 192 dots vert.
With Apple IIGS: 640 dots horizontally by 200 dots vertically

Text display

- both monitors: up to 80 columns by 25 lines

Horizontal linearity

- both monitors: less than 10%

Vertical linearity

- both monitors: less than 7%

Video Input Connector

- both monitors: RCA-style phone jack (75 ohm)

Controls

- Apple Monochrome Monitor IIe
Front: power on/off, contrast
Rear: brightness, vertical hold, height
- Apple Monochrome Monitor
Side: power on/off, contrast
Rear: brightness, vertical hold, vertical amplitude

Electrical Requirements

- both monitors:
Line voltage 108 to 132 volts AC
Frequency 50 to 60 hertz
Power consumption
 Typically less than 20 watts
 Maximum 45 watts

Environmental requirements

- Apple Monochrome Monitor IIe
Operating temperature: 41 to 104 degrees F (5 to 40 degrees C)
Maximum humidity: 90%
Altitude: 0 to 10,000 ft. (0 to 3,048 m)
- Apple Monochrome Monitor
Operating temperature: 32 to 122 degrees F (0 to 5 degrees C)
Maximum humidity: 90%
Altitude: 0 to 10,000 ft. (0 to 3,048 m)

Dimensions

- Apple Monochrome Monitor IIe
Height: 10.63 in. (27.0 cm)
Width: 14.56 in. (37.0 cm)
Depth: 12.50 in (31.8 cm)
Weight: 18 lbs. (8.16 kg)
- Apple Monochrome Monitor
Height: 10 in. (25.5 cm)
Width: 12.3 in. (31.0 cm)
Depth: 14.3 in (37.5 cm)
Weight: 18 lbs. (8.16 kg)

Copyright 1991 Apple Computer, Inc.

Keywords: SPECSHT

=====

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 7888