



Tech Info Library

GS/OS: Setting the Finder as the Startup Application

This article last reviewed: 7 August 1990

TOPIC -----

My school district has an Apple IIGS network.

I want to change the startup application from Aristotle to the GS/OS 5.0.2 Finder. I tried to set "Finder" as the startup and got an error, "Unable to load descriptor \$004E".

I set the appropriate permissions for access to the GS/OS operating system folder on the server, but I got the same error.

Can you help?

DISCUSSION -----

The \$004E error indicates that GS/OS attempted an invalid access procedure. There was only one way we were able to duplicate this error -- by denying access privileges to the Icons folder on the server. When the access privileges on the Icons folder weren't set to See Folders/See Files for everyone, the "Unable to load descriptors" message appeared. Descriptor refers information stored in files within the Icon folder, which is needed by the Finder. Once we reset the Icon folder privileges so See Folders/See Files were allowed for everyone, startup proceeded normally.

Once access is granted to the Icons folder on the server and Finder is set as the startup application in the server's Admin program, the startup process should continue until you reach the Finder's desktop.

IMPORTANT NOTE: When using the "Icon Info" menu item from the GS/OS "Special" menu, there is one step that is sometimes forgotten. Be sure to press the "Apply" button while on the "Access" card of the "Icon Info" dialog box after making any changes to access privileges. If this button is not pressed, the changes are not recorded and the privileges revert to the previous settings.
Copyright 1990 Apple Computer, Inc.

Keywords: <None>

=====

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 5990