



Tech Info Library

BASIC: APPEND fix (2 of 2)

For those who do not feel comfortable with the above machine language, use the following procedure to make new slave diskettes with the corrected DOS:

1. Boot the system with an initialized diskette. This loads the old DOS into your Apple.
2. Type in the BASIC program below and RUN it. This will change the old DOS in memory to the corrected DOS.
3. SAVE this program just in case you made a typo.
4. Without rebooting the system, run the 4 test programs above to see if APPEND works correctly.
5. Type NEW; insert a blank diskette, and type INIT HELLO. This creates a diskette with the corrected DOS.
6. Use this new diskette whenever initializing other diskettes; the corrected DOS will be carried over.

Use this BASIC program in step 2 above:

```
10 POKE -18813,76 : POKE -18812,179 : POKE -18811,182
20 FOR I = -18765 TO -18738
30 READ A: POKE I,A: NEXT
40 FOR I = -17788 TO -17773
50 POKE I,0: NEXT
60 PRINT "DONE..."
75 END
80 DATA 173,189,181,141,230,181,141,234,181,173,190,181,141,231,
      181,141,235,181,141,228,181,186,142,155,179,76,127,179
```

Apple Technical Communications

Keywords: <None>

=====
This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 331