



Tech Info Library

ProDOS: Error 900 When Using Apple IIc Sys Utilities Disk (9/95)

Article Created: 17 December 1984

Article Reviewed/Updated: 19 September 1995

TOPIC -----

I started up my system with the Apple IIc System Utilities Disk. This disk has a new port configuration saved to it. If I select any menu option then press the Escape key to return to the main menu, I always drop into the monitor with Error #900 displayed. How can I get around this?

DISCUSSION -----

The workaround is as follows:

Step 1

Duplicate your Systems Utilities disk: select the main menu option 5. Boot your system with this new copy.

Step 2

Select main menu option 9 to exit from System Utilities.

Step 3

From the Basic prompt, type in the following:

```
Load SU,S6
```

```
List 900
```

You will see the listing:

```
900 Call 768: Poke 216,0: Onerr Goto 930
```

Step 4

Change line 900 to:

```
900 Poke 216,0: Onerr Goto 930: Call 768
```

Step 5

Enter the following commands to unlock the file, save the changes to disk and
relock the file to prevent accidental damage:

List 900

Step 6

Check once again that line 900 reads properly as in step 4, then type:

Unlock SU,S6

Save SU,S6

Lock SU,S6

Article Change History:

19 Sep 1995 - Reformatted it to meet current standards

Support Information Services

Apple Technical Communications

Keywords: <None>

=====

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 899