



Tech Info Library

AppleWriter WPL: Using AUTOLETTER to print mailing lables

You can use AppleWriter to print out mailing labels, using the address list of the WPL program AUTOLETTER that resides on the AppleWriter master diskette. Modify AUTOLETTER so that it reads as follows:

```
START   PSX1
LOOP    NY
        L .D1/FORMLETTER
        B
        F/(ADDRESS)//
        Y$
        L .D1/ADDRS!<(X)>!<!N
        PGO FOUND
        PGO QUIT
FOUND   PNP
        PSX +1
        PGO LOOP
QUIT    PIN Done at address (X) (press return)
        NY
```

1. Save this as AUTOLABELS on the disk with the form letter and address list.
2. Press CTRL-N, type y, and press RETURN.
3. Type in the following four lines, which show carriage returns:

```
(ADDRESS)]
]
]
]
```

4. Save this file as FORMLETTER on the disk with AUTOLABELS.
5. Press CTRL-N, type y, and press RETURN.
6. Make sure that your printer parameters are set at the following:

```
Printed Lines (PL)=4
Page Interval (PI)=4
```

The rest of the printer parameters must be set in accordance with the printer you are using.

You can now run the AUTOLABELS program in the same way you run any WPL program. Remember, the file to run is AUTOLABELS, not AUTOLETTER. Make sure that the disk with AUTOLABELS, FORMLETTER AND ADDRIS is in the internal drive on an Apple III or in the current prefix volume on a IIe or IIc.

Apple Technical Communications

Keywords: <None>

=====

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 1296