



Tech Info Library

UPIC: Interfacing the C. Itoh 8510A printer

This is the cable configuration to connect an Apple III Universal Parallel Interface card to a C.Itoh 8510A printer.

Universal Parallel Interface		C.Itoh 8510A	
Pin	Function	Pin	Function
1	Shield Ground	17	Chassis Ground
2	Acknowledge	10	Acknowledge
3	Not used	-	Not connected
4	Not used	-	Not connected
5	Not used	-	Not connected
6	Printer in check	32	Fault
7	Not used	-	Not connected
8	Strobe out	1	Strobe in
9	Printer empty	12	Printer empty
10	Data bit 0 (LSB)	2	Data bit 0
11	Data bit 1	3	Data bit 1
12	Data bit 2	4	Data bit 2
13	Data bit 3	5	Data bit 3
14	Data bit 4	6	Data bit 4
15	Data bit 5	7	Data bit 5
16	Data bit 6	8	Data bit 6
17	Data bit 7 (MSB)	9	Data bit 7
18	Printer on-line	18	Select
19	Printer Power-on	19	+5 volt
20	Signal Ground	16	0 volt

Apple III Universal Parallel Printer driver configuration block:

```

ERRMASK:      E8
ERRSTAT:      C8
AUTOLF:       40
CTRLWRD:      00
TIMEOUT:      0A

```

C.Itoh 8510A Switch selection:

```

Switch one:           Switch two:
1 2 3 4 5 6 7 8      1 2 3 4 5 6 7 8
0 1 0 0 0 1 1 1      0 0 0 0 0 0 1 0

```

Keywords: <None>

=====
This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 623