



Tech Info Library

Using Catalyst 2.0 with the Apple III and hard disk drives

To use Catalyst 2.0 with the Apple III and hard disk drives other than the ProFile, you need to change the driver configuration block of the .CATALYST driver as follows:

```

00 01 02 03 04 05 06 07 08 09 0A 0B 0C 0D 0E 0F 10 11
-- -- -- -- -- -- -- -- -- -- -- -- -- -- -- --
(See notes just below) 00 8F 97 8A 91 93 23 17 17 F6 00 B8

```

Notes:

- 00 - Slot number
- 01- Unit number
- 02 - Type
- 03 - Sub Type
- 04 - Low Byte, Manufacturer's ID
- 05 - High Byte, Manufacturer's ID

For a 10 megabyte ProFile, copy the information in bytes 00 through 05 from the existing Catalyst hard disk driver configuration block (DCB) of the Catalyst driver that you are using. For a 10 MB Profile, the DCB should look like this:

```

00 01 02 03 04 05 06 07 08 09 0A 0B 0C 0D 0E 0F 10 11
-- -- -- -- -- -- -- -- -- -- -- -- -- -- -- --
slot 00 01 01 23 00 00 8F 97 8A 91 93 23 17 17 F6 00 B8

```

For a 5 MB Profile, the DCB should look like this:

```

00 01 02 03 04 05 06 07 08 09 0A 0B 0C 0D 0E 0F 10 11
-- -- -- -- -- -- -- -- -- -- -- -- -- -- -- --
slot 00 D1 01 23 00 00 8F 97 8A DD 93 23 E8 17 F6 3B C3

```

Apple Technical Communications

Keywords: <None>

=====

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 264