



# Tech Info Library

## Personal LaserWriter NTR for Windows: Specs (Discontinued)

Article Created: 5 April 1993

TOPIC -----

This article gives technical specifications for the Personal LaserWriter NTR for Windows.

DISCUSSION -----

### Marking Engine

-----

- Canon LBP-LX laser-xerographic

### Controller

-----

- 16 MHz AMD AMD29005 RISC processor

### Memory

-----

- 3MB ROM
- 3MB RAM, upgradable to 4MB

### Speed

-----

- 4 pages per minute, maximum

### Print Quality

-----

- 300 dpi for text and graphics

### Fonts

-----

- 75 scalable fonts
  - 35 fonts in ROM from the following font families: ITC Avant Garde Gothic, ITC Bookman, Courier, Helvetica, Helvetica Narrow, New Century Schoolbook, Palatino, Symbol, Times, ITC Zapf Chancery, and ITC Zapf Dingbats
  - 40 additional Windows 3.1-compatible fonts on disk from the Bitstream TrueType Font Pack, including fonts from the following families: Bitstream Oz Handicraft, Clarendon, English, Fraktur, Freehand, Geometric, Humanist, Huxley Vertical, Imperial, Impress, Incised, Informal, Nuptial,

- Poster Bodoni, Revival, Square Slabserif, Staccato, Umbra, and Vineta
- Any TrueType or PostScript fonts

#### Interfaces

- 
- Simultaneous connection to Centronics-type parallel, RS-232 serial, and LocalTalk interfaces

#### Paper Feed

- 
- Automatic or manual with integral multipurpose tray
  - Automatic with optional Personal LaserWriter 250-sheet Cassette Base and the Letter Cassette, Legal Cassette, Envelope Cassette, A4 Cassette, or B5 Cassette

#### Print Materials

- 
- 16-lb to 28-lb (60- to 105-g/m<sup>2</sup>) paperbond
  - Paper: U.S. letter, U.S. legal, A4, B5
  - Most letterhead and colored stock, labels, and envelopes
  - Medium-weight photocopier transparencies
  - Envelopes:
    - minimum 3.8 x 7.25 inch (96 x 184 mm)
    - maximum 7.4 x 10 inch (188 x 255 mm)

#### Paper Capacities

- 
- Cassette: up to 70 sheets of 20-lb. (75-g/m<sup>2</sup>) paper
  - Optional paper cassette: 250 sheets of 20-lb. (75-g/m<sup>2</sup>) paper
  - Optional envelope cassette: 15 envelopes

#### Printable Surface

- 
- Maximum printable line: 8.0 in. (203.2 mm)
  - Minimum margins: 0.25 in. (6.35 mm) (actual printable area may vary depending on the application)

#### Size and Weight

- 
- Height: 8 inches (20.3 cm)
  - Width: 15 inches (38 cm)
  - Depth (with optional letter-size cassette): 18.3 inches (46.4 cm)
  - Weight: 29.5 lb. (13.35 kg)

#### Power Requirements

- 
- U.S./Japan: 90 to 110 volts AC, 48-52Hz, 58-62 Hz
  - Europe/Australia: 220 to 240 volts AC, 48-52 Hertz

#### Maximum Power Consumption

- 
- 600 watts at 115 volts
  - 550 watts at 220 volts

Operating Environment

- Temperature: 50 to 90° F (10 to 32.5° C)
- Humidity: 20% to 80% noncondensing
- Toner cartridge transit environment: -4 to 140° F (-20 to 40° C)

Copyright 1993-1994, Apple Computer, Inc.

Keywords: SPECSHT

=====  
This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 11771