



Tech Info Library

LaserWriter Select 310 for Windows: Specifications (4/93)

Article Created: 5 April 1993

TOPIC -----

This article provides technical specifications for the LaserWriter Select 310 for Windows.

DISCUSSION -----

Marking Engine

- Fuji Xerox laser

Controller

- AMD AM29205 RISC processor

Memory

- 1.5MB RAM, expandable to 5.5MB
- Optional 1MB and 4MB upgrades

Speed

- Five pages per minute (maximum)

Interfaces

- Centronics-type parallel port
- RS-422 serial 8-pin DIN port

Print Quality

- 300 dpi for text and graphics

Fonts

- Includes 53 scalable fonts:
 - 13 fonts in printer ROM from the following families: Courier, Helvetica, Times, and Symbol

- 40 additional Windows 3.1-compatible fonts on disk from the Bitstream TrueType Font Pack, including fonts from the following families: Bitstream Oz Handicraft, Clarendon, English, Fraktur, Freehand, Geometric, Humanist, Huxley Vertical, Imperial, Impress, Incised, Informal, Nuptial, Poster Bodoni, Revival, Square Slabserif, Staccato, Umbra, and Vineta
- Any PostScript font

Size and Weight

- Height: 8 in. (25.3 cm)
- Width: 15 in. (38 cm)
- Depth: 18.3 in. (45 cm)
- Weight: 26 lb. (12 kg)

Operating Environment

- Temperature: 50 to 90° F (10 to 32° C)
- Humidity: 20% to 80% noncondensing
- Toner cartridge transit environment: -4 to 104° F (-20 to 40° C)

Power Requirements

- U.S./Japan: 100 to 115 V, 50 to 60 Hz
- Europe/Australia: 220 to 240 V, 50 Hz

Power Consumption

- 450 W maximum at 115 V or 220 V

Copyright 1993, Apple Computer, Inc.

Keywords: SPECSHT

=====
This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 11775