



# Tech Info Library

## ARA 2.0: Requirements, Remote Access MultiPort Server (5/95)

Article Created: 15 November 1993

Article Reviewed/Updated: 24 May 1995

TOPIC -----

This article describes the minimum requirements for using the Remote Access MultiPort Server.

DISCUSSION -----

### Hardware requirements

The following are the hardware requirements for setting up and running a Remote Access MultiPort Server:

- Any Macintosh computer with slots for 12-inch NuBus cards and an Apple SuperDrive for high-density floppy disks.
- 5MB RAM for a 4-port server; 8MB RAM for a 16-port server
- A hard disk
- An Apple Remote Access Serial Card and an Apple RS-232 cable
- One or more high-speed modems
- A telephone line for each modem

### Software requirements

Your Remote Access MultiPort Server package includes installer disks, which contain all the software you need to run the Remote Access MultiPort Server and Remote Access Manager application. Additionally, you must be running system software version 7.0 or later on your server computer (7.1 is recommended).

Macintosh clients need to run System 7 and should have either Apple Remote Access Personal Service for Macintosh version 2.0, or Apple Remote Access Client for Macintosh version 2.0 software installed.

### Network requirements

Connect your Remote Access MultiPort Server to an AppleTalk network using the same type of networking software and cable types as used with other devices on your network. Any AppleTalk network is capable of supporting a Remote Access MultiPort Server. The most common network choices are LocalTalk, Ethernet, and Token Ring.

Article Change History:

24 May 1995 - Reviewed for technical accuracy.

Support Information Services

Copyright 1993-95, Apple Computer, Inc.

Keywords: <None>

=====

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 13930