



Tech Info Library

Internet Router: Correction to Administrator's Guide

This article last reviewed: 8 SSeptember 1989

TOPIC -----

On page 129, of the AppleTalk Internet Router Administrator's Guide, (Appendix A: Planning an AppleTalk Internet, Figure A-8) it appears that the cable segments are LocalTalk (printer is on the same cable segment) and the workstations are all LocalTalk.

How do you get workstations and printers physically connected to the router via LocalTalk to be in separate zones as the picture describes?

How do you build a work group consisting of a few LocalTalk users, LocalTalk printers, and some EtherTalk users in one zone?

The only workstation zone selectable under the Apple-Control Panel-Network is for EtherTalk and TokenTalk? Is this correct? Is the zone for the LocalTalk printers always the single LocalTalk zone name?

DISCUSSION -----

The diagram on page 129 of the "AppleTalk Internet Router Administrator's Guide" is misleading. A LocalTalk network can be associated with only one zone. This is the same as it was with AppleTalk Phase 1.

With AppleTalk Phase 2, any node on an AppleTalk network (other than LocalTalk) can belong to any zone selected from a list of available zone names. This would include EtherTalk 2.0 and TokenTalk 2.0. More information on this is on page 4 of the "AppleTalk Phase 2 Introduction and Upgrade Guide".
Copyright 1989 Apple Computer, Inc.

Keywords: <None>

=====

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 4405