



# Tech Info Library

## AppleTalk: Description of SP\_INIT and SP\_GET\_SESSION

This article last reviewed: 3 June 1988

Some users involved in AppleTalk programming have asked for more information about some of the ASP routines described in "Inside AppleTalk" -- especially SP\_INIT and SP\_GET\_SESSION.

The SP\_INIT and SP\_GET\_SESSION routines have been more completely documented in the newest printing of Inside AppleTalk (July 14, 1986).

Here is a reprint of the SP\_INIT and SP\_GET\_SESSION documentation from section XI, pages 6 and 7:

Before any workstation can open a session with a server, the server's SLS must be established. This must be done by the ASP client at the server end. This client must issue an OPEN-ATP-Responding-socket call to create the SLS. Then it must call NBP to register the appropriate server entity name on this socket. At this point, the SLS is set up so that a workstation can discover its own network address through an NBP lookup.

However, a workstation still cannot open sessions with this client entity. For this purpose, the ASP client in the server must now issue an SPInit call to ASP (passing to ASP the network address, known as the SLSEntityIdentifier), followed by one or more SPGetSession calls.

### SP\_Init

#### Inputs:

SLSEntityIdentifier -- SLS network identifier  
ServiceStatusBlock -- block with status information  
ServiceStatusBlockSize -- size of status information block

#### Outputs:

SPError -- error code returned by ASP  
SLSRefNum -- reference number for SLS

#### Errors:

TooManyClients -- ASP implementation cannot support another client

SizeErr -- ServiceStatusBlockSize is greater than QuantumSize

This call is issued by the ASP client after having opened and named the SLS. The call passes the (network-dependent) SLSEntityIdentifier to ASP as well as a ServiceStatusBlock. This block is used to hold the service status information to be returned in reply to GetStatus request received at the SLS. The SLSEntityIdentifier is the complete internet address of the SLS.

SPInit returns the SLSRefNum (this is unique among all SLSs on the same server node) that is used in the SPGetSession call to make reference to the SLS passed in the SPInit call.

#### SP\_Get\_Session

##### Inputs:

SLSRefNum -- reference number for the SLS

##### Outputs:

SPErrror -- error code returned by ASP  
SessRefNum -- session reference number

##### Errors:

ParamErr -- unknown SLSRefNum  
NoMoreSessions -- implementation cannot support another session

This call is issued by the ASP client to allow it to accept an OpenSession command received on the SLS identified by the SLSRefNum. Each SPGetSession request authorizes ASP to accept one more OpenSession request.

The call completes when such a request is received on the SLS and a corresponding session has been opened. The SessRefNum is returned to the server ASP client and must be used in all further calls to ASP that refer to this session.

Clearly, the SessRefNum must be unique among all sessions open to the server.

Copyright 1988 Apple Computer, Inc.

Keywords: specsht

=====

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 3045