



Tech Info Library

Inter•Poll: How to Identify Active Apple II Systems

This article last reviewed: 17 March 1989

Certain requirements must be met before Inter•Poll can identify an Apple II on a network:

Apple IIGS

For an Apple IIGS to appear in the "Device List" window of Inter•Poll, you must:

1. Select "Built-in AppleTalk" from the Control Panel. At the same time, set the port that the network is connected to, generally the Printer port, to "Your Card".
2. Shut down and restart the system.
3. Run Inter•Poll on the Macintosh, or have it running and checking the network. The Apple IIGS should show up in the Device List window.

Apple IIe

1. Install Apple II WorkStation card in slot 7 of Apple IIe and connect LocalTalk port to network.
2. Start up system and log into a ProDOS server on the network. Once the system gets past the Password screen, the device shows up in the Device List window of Inter-Poll.

The important requirements are:

- Having Built-in AppleTalk selected in the Control Panel of the Apple IIGS
- Having the proper port set to "Your Card" on the Apple IIGS
- Being past the Password screen on an Apple IIe with WorkStation Card.

Copyright 1989 Apple Computer, Inc.

Keywords: <None>

=====

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 3690