



Tech Info Library

AppleLine: Specifications (Discontinued)

Article Created: 14 March 1991

Electrical/Communications

- Emulation: 3278 Model 2, requiring the use of VT100 emulation software
- Serial port: RS-232-C with autobaud feature
- Data format: serial asynchronous; 7- or 8-bit selectable
- Data rate: 45.5 to 19.2K baud
- Communications: Full-duplex interface
 - Category A device requiring type A terminal adapter and BNC coaxial connector
 - 15 ft. (5 m) maximum distance between AppleLine and Apple computer (when RS-232 cable is used)
 - 5000 ft (1500 m) maximum distance between AppleLine and 3274/76 controller
- Power supply: 120 VAC, wall-mounted transformer
- Temperature range: 50 to 104 degrees F (10 to 40 C)

Mechanical

- Width: 8.62 in. (21.91 cm)
- Height: 2.22 in. (5.64 cm)
- Depth: 12.7 in. (32.26 cm)
- Weight (including packing materials): 4 lb. (1.8 kg)
- Side panel: Off/On switch
- Rear panel: DB-25-pin connector, coaxial connector, and non-shorting power jack

Copyright 1991, Apple Computer, Inc.

Keywords: SPECSHT

=====
This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 6955