



Tech Info Library

ImageWriter Printer Configuration Table

This article last reviewed: 02 November 1988

System	SW-1 12345678	SW-2 1234	CABLE REQUIRED Part Number
Apple III	11001100	1100	590-0029 and 590-0037B
Macintosh	11001100	1100	590-0169
Lisa/Macintosh XL	11001100	1100	590-0029 and 590-0037B
Apple IIc	11001100	1100	590-0191A
Super Serial	11001100	1100	590-0037B
High Speed Serial	11001100	0011	590-0037B

NOTE: 0 = OFF = OPEN
 1 = ON = CLOSED

Apple III Driver Configuration

Driver	Data Configuration Block											
	0	1	2	3	4	5	6	7	8	9	A	B
RS232	0E	00	00	00	00	00	13	11	DF	84	50	80
PRINTER	0E	00	00	00	00							

Super Serial Card Configuration

	1	_2_	_3_	_4_	_5_	_6_	_7_
SW1	Off	Off	Off	On	Off	On	On
SW2	On	Off	Off	Off	On	Off	Off

NOTE: Jumper block should be pointing towards terminal.

High Speed Serial Card Configuration

_____ |_1_|_2_|_3_|_4_|_5_|_6_|_7_|
Switches | On|Off|On |On |Off|Off|Off|

NOTE: The High Speed card must have the PROM P8 installed.
Copyright 1988 Apple Computer, Inc.

Keywords: HTS,CNFG

=====

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 1427