

# Tech Info Library

# Macintosh IIx: Specifications (Discontinued 10/90)

Article Created: 15 March 1991

Article Reviewed/Updated: 20 July 1992

TOPIC -----

This article provides technical specifications for the Macintosh IIx computer.

DISCUSSION -----

#### PROCESSOR

- 68030; 32-bit internal
- Harvard architecture
- 15.667 MHz clock speed
- 256-byte instruction and data caches

#### COPROCESSOR

- 68882 floating-point coprocessor (IEEE standard: 80-bit precision)
- 15.667-MHz clock speed

#### INTERFACES

- Six NuBus internal slots support full 32-bit address and data buses.
- Two mini-8 serial (RS-232/ RS-422) ports
- Two Apple Desktop Bus ports allow daisy-chaining of multiple peripheral devices with a SCSI interface: uses a 50-pin connector (internal) and a DB-25 connector (external)
- Sound jack for stereo output

## MOUSE

- Mechanical tracking: optical shaft encoding at 3.94+/-0.39 pulses per mm (100 -+10 pulses/in.) of travel

#### SOUND GENERATOR

- Apple's custom digital-sound chip provides 8-bit stereo sampling at 44.1 KHz, and includes four-voice, wave-table synthesis. Capable of driving stereo headphones or other stereo equipment through the sound jack.

# ELECTRICAL REQUIREMENTS

- Line voltage: 100 to 240 VAC, automatically configured
- Frequency: 48 to 62 Hz
- Maximum power: 230 W, not including monitor power

### SIZE AND WEIGHT

- MAIN UNIT
  - Height: 5.5 in. (14.0 cm) - Width: 18.7 in. (47.4 cm)
  - Depth: 14.4 in. (36.5 cm)
  - Weight: 24 lb. (10.9 kg, not including hard disk drive)

### - MOUSE

- Height: 1. I in. (2.8 cm) - Width: 2.1 in. (5.3 cm) - Depth: 3.8 in.(9.7 cm) - Weight: 6 oz. (17 kg)

Copyright 1991, Apple Computer, Inc.

Keywords: SPECSHT

\_\_\_\_\_

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 6973