



Tech Info Library

Apple Ethernet LC & LC Twisted-Pair Cards Specifications (1/94)

Article Created: 5 January 1994

TOPIC -----

This article provides the specifications for the Apple Ethernet LC Card and the Apple Ethernet LC Twisted-Pair Card.

DISCUSSION -----

Apple Ethernet LC Card

Connector

- Apple Ethernet

Transmit/receive data rate

- 10-megabit-per-second maximum data rate

Environmental requirements

- Operating temperature: 50° to 104° F (10° to 40° C)
- Humidity: 20% to 95% noncondensing

Power dissipation

- 4 W or less

Ethernet controller

- National Semiconductor DP83932 -SONIC

System requirements

- One available Macintosh LC-compatible processor-direct slot
- Appropriate Apple Ethernet cable system media adapter

Apple Ethernet LC Twisted-Pair Card

Connector

- Ethernet 10Base-T compliant RJ-45 port

Transmit/receive data rate

- 10-megabit-per-second maximum data rate

Environmental requirements

- Operating temperature: 50° to 104° F (10° to 40° C)
- Humidity: 20% to 95% noncondensing

Power dissipation

- Maximum 1.5, average 1 W

Ethernet controller

- National Semiconductor DP83934 -SONIC-T

System requirements

- One available Macintosh LC-compatible processor-direct slot
- Unshielded twisted-pair cable
- IEEE 802.3-compatible 10Base-T hub

Copyright 1994, Apple Computer, Inc.

Keywords: <None>

=====

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 14358