



# Tech Info Library

## PowerBook 540c: Specifications (5/96)

Article Created: 2 May 1994

Article Reviewed/Updated: 31 May 1996

TOPIC -----

This article provides technical specifications for the PowerBook 540c computer.

DISCUSSION -----

Provides Macintosh Quadra performance in an all-in-one notebook computer

### Microprocessor

-----

- 66/33-MHz 68LC040 microprocessor (no FPU). (the two speeds refer to the internal processor and bus interface, respectively)
- 32-bit Address and Data bus
- Daughterboard (memory expansion) has a 32-bit bus running at 33MHz

### RAM

---

- 4 MB RAM on logic board.
- Expandable to 36 MB with 70ns low power self-refreshing RAM (Apple 8 MB RAM Expansion Kit, or Third Party higher density RAM card)

### Storage

-----

- One built-in 1.4 MB Apple SuperDrive disk drive that uses high-density floppy disks; it reads, writes, and formats Macintosh, MS-DOS, OS/2, and ProDOS disks.
- One internal 320 MB hard disk.

### Display/Video Out

-----

- 9.5-inch (diagonal), backlit, active matrix color display
- 640 x 480 pixels, with 256 colors by 400 pixels with thousands of colors
- Sleeps on close
- User-configurable
- External display port (mini DB-15) supports 8-bit video
- External display options:
  - Macintosh 12" Monochrome Display
  - Macintosh 12" RGB Display

AppleColor High Resolution RGB Display

Macintosh Color Display

Macintosh 16" Color Display

Macintosh Portrait Display

Some VGA and SVGA monitors (third party adapter required)

- Two video-out modes:
  - Video mirroring for simultaneous display of the same image on two screens.
  - Dual display for full use of both screens.

#### Networking

- Serial/LocalTalk
- Built-in High Speed Ethernet with Apple AUI connector

#### System Software

- Requires System 7.1.1 or later (5 High Density Disks)
- PowerBook 500 Series Enabler version 1.0.2 or later

#### Battery

- Nickel-metal-hydride PowerBook Intelligent Batteries each provide up to 3.5 hours of use before recharge.
- EverWatch battery-saver technology
- Batteries recharge in two hours when computer is in sleep or shutdown; four hours when running.
- PowerBook Control Strip allows user to monitor time remaining, charge time, and battery usage
- Backup rechargeable lithium battery maintains RAM in sleep mode while main battery is removed for up to three minutes.

#### Keyboard and Tracking Device

- Built-in keyboard with standard size keyboard with 76 (US) or 77 (ISO) keys including 12 function keys
- Two-level tilt adjustment
- Power-on key located on Keyboard
- Solid-state trackpad provides precise cursor control in response to the user's fingertip over its surface

#### Clock/Calendar

- CMOS custom chip with long-life lithium battery.

#### Microphone

- Built-in omnidirectional; output voltage is 4 mV, peak to peak, at normal volume

#### Interfaces

- One Apple Desktop Bus (ADB) port for keyboard, mouse, and other devices.

- One RS-422 serial port for LocalTalk networking, printers, modems, and other devices.
- One high-speed Ethernet port
- One HDI-30 SCSI port for hard disks, scanners, CD-ROM drives, and other devices (up to 6 devices can be chained).
- One slot for optional modem.
- One video-out port, supporting 8 bit density and 256 colors.
- One stereo sound output port for external audio amplifier or headphones.
- One mono sound-in port.
- Security slot for use with third-party equipment to lock the computer.
- 90-pin processor direct slot (PDS) for connecting PDS devices or optional PowerBook PCMCIA Expansion Module allows use of two Type II or one Type III PCMCIA-type card).
- One RAM slot

#### Modem

-----

- Optional Global Village PowerPort Mercury modem supports 19,200 bps data transmission and 14,400 bps fax

#### Built-in Stereo Sound

-----

- CD-quality, 16-bit stereo sound capable of driving headphones or other stereo equipment.
- Two built-in stereo speakers
- Digital-to-analog and analog-to-digital conversion sampled at 11.035, 22.050, or 44.100 kHz.

#### Disability Access

-----

- Easy Access and the ability to substitute visual cue for beep included with system software. These built-in solutions and third-party options provide alternative input and output devices for people with disabilities.

#### ADB Power Requirements

-----

- Maximum current draw for all ADB devices is 200 mA (a maximum of three ADB devices is recommended)

#### Electrical Requirements

-----

- Line voltage: 100 to 240 volts, 50 to 60 Hz

#### Environmental Requirements

-----

- Operating temperature: 50 to 104° F (10 to 40° C)
- Storage Temperature: -40°F to +149°F (-40 to +65° C)
- Relative humidity: 20% to 80% noncondensing
- Altitude: max. 10,000 ft. (3,048 m)
- Maximum Storage Altitude: 15,000 ft. (4,722 m)

#### Size and Weight

- 
- Height: 2.3 in. (5.7 cm)
  - Width: 11.5 in. (29.2 cm)
  - Depth: 9.7 in. (24.5 cm)
  - Weight: 7.3 lb. (3.3 kg)

#### Noise Level

- 
- Noise free except for disk drive use.

#### Security

- 
- Slot for security cable

#### Ordering Information

##### Ordering Information

PowerBook 540c 4/320

Order No. M2809LL/A

- PowerBook 540 computer with 4MB of RAM, built-in 1.4MB Apple SuperDrive, and internal 240MB hard disk drive
- Two PowerBook Intelligent Batteries and AC adapter
- System 7
- Complete setup, learning, and reference documentation
- Training software
- Limited warranty
- PowerBook Mobility Bundle

Order No. M3727LL/A

Same as Order No. M2809LL/A, but with 12 MB of RAM, 500 MB hard drive and a Global Village PowerPort Mercury Fax/Data Modem.

PowerBook 8MB Memory Expansion Kit

Order No. M1913LL/A

PowerBook Intelligent Battery

Order No. M1908LL/A

PowerBook AC Adapter

Order No. M1910LL/A

PowerBook PCMCIA Expansion Module

Order No. M2995LL/C

Apple HDI-30 SCSI Disk Adapter

Order No. M2539LL/A

Apple HDI-30 SCSI System Cable

Order No. M2538LL/A

#### Article Change History:

31 May 1996 - Updated part number.

12 May 1995 - Clarified speed of daughter board.  
12 Dec 1994 - Additional configuration documented.

Copyright 1994-96, Apple Computer, Inc.

Keywords: specsht,kpbook

=====

This information is from the Apple Technical Information Library.

19960603 14:32:16.00

Tech Info Library Article Number: 15284