

# Macintosh PowerBook 5300ce/117:Technical Specifications (8/96)

Article Created: 21 August 1995 Article Reviewed/Updated: 1 August 1996

TOPIC -----

This article contains a list of technical specifications for the Macintosh PowerBook 5300ce/117 computer.

DISCUSSION -----

## Microprocessor

#### \_\_\_\_\_

• 117-MHz PowerPC 603e

## Memory

- ----
- 32 MB of RAM, expandable to 64 MB (Note: 16 MB is soldered to the logic board. The other 16 MB is in the one RAM card expansion slot.)

## Storage

-----

- Built-in removable Apple SuperDrive 1.4 MB floppy disk drive, which uses high-density floppy disks and reads, writes, and formats Macintosh, Windows, MS-DOS, OS/2, and ProDOS disks
- Internal 1.1 GB hard disk drive
- Expansion bay for third-party solutions such as an additional hard disk drive or magneto-optical drive (PC Card storage tray included in box may be inserted into this bay to reduce weight by 0.4 lb.)

# Display

-----

- 10.4-in. (diagonal), backlit, active-matrix, SVGA color display
- Resolution: 800 by 600 pixels with thousands of colors; 800 by 600 resolution (SVGA) provides a larger viewing area than standard 640 by 480 displays. This means you see more spreadsheet columns, text, and graphics
- Black matrix screen reduces glare, clearly defines colors, and improves contrast

Battery

\_\_\_\_

- Nickel-Metal-Hydride battery provides 2.5 4 hours of use before recharge
- Battery recharges in 2 hours while computer is shut down or in sleep mode; 4 hours while running
- PowerBook Control Strip lets you monitor time remaining, charge status, and battery usage

PC Card slots (PCMCIA)

------

- Two PC Card slots that can accommodate two Type I or II PC Cards or one Type III PC Card
- Lets you add industry-standard cards such as Ethernet networking, a wired or wireless modem, storage, or other capabilities

#### Expansion bay

\_\_\_\_\_

- IDE connector for third-party solutions such as an additional hard drive, a magneto-optical drive, and other devices
- Power lines for connection of an internal AC adapter and other third-party solutions

# Ports

\_ \_ \_ \_ \_

- One Apple Desktop Bus (ADB) port
- One serial (RS-422) port
- One SCSI port for connecting as many as six external devices (including CD-ROM)
- One power adapter port
- Stereo sound input port
- Stereo sound output port
- Video output port

# Networking

#### -----

- Serial/LocalTalk port for AppleTalk connections to networks and printers
- Ethernet networking through PC Cards
- Ultra-easy file sharing through infrared technology-without cable connections or time-consuming setup; supports AppleTalk protocol

### Built-in Stereo Sound

\_\_\_\_\_

- 16-bit, CD-quality stereo sound capable of driving headphones or external speakers
- Built-in speaker and integrated microphone
- Digital-to-analog conversion sampled at 44.1, 22.05, or 11.025 kHz
- 16 bit, audio line-in for recording

# Video Output

-----

• 8-bit video output port to support external color displays-compatible with most Apple, VGA, and SVGA monitors (upgradable to greater bit depths through third-party solutions)

Security

#### \_\_\_\_\_

- Includes a security slot that secures the system, battery, and expansion bay (requires a third- party accessory)
- Includes password protection software

Keyboard and Apple trackpad

-----

- Built-in, full-size keyboard with 76 (U.S.) or 77 (ISO) keys, including 12 function keys and integrated palm rest
- Power button on keyboard
- Solid-state Apple trackpad provides precise cursor control in response to the movement of the user's fingertip over its surface; sensing of movement and acceleration is easily adjustable through a control panel

#### Disability access

\_\_\_\_\_

• System software includes CloseView and Easy Access, and provides the ability to substitute visual cue for beep

Electrical requirements

#### \_\_\_\_\_

- Line voltage: 100 to 240 volts AC
- Frequency: 50 to 60 Hz

ADB power requirements

\_\_\_\_\_

• Maximum current draw for all ADB devices: 200 mA

Environmental requirements

-----

- Operating temperature: 41 degrees to 95 degrees F (5 degrees to 35 degrees C)
- Storage temperature: -13 degrees to 140 degrees F (-25 degrees to 60 degrees C)
- Relative humidity: 20% to 80% noncondensing
- Operating altitude: 0 to 10,000 ft. (0 to 3,048 m)
- Maximum storage altitude: 15,000 ft. (4,722 m)

Size and weight

- -----
- Height: 2.2 in. (5.3 cm)
- Width: 11.5 in. (29.2 cm)
- Depth: 8.5 in. (21.6 cm)
- Weight: 6.2 lb. (2.8 kg)

Article Change History: 01 Aug 1996 - Added keyword. 04 Oct 1995 - Updated battery information. 25 Aug 1995 - Reviewed for technical accuracy.

Copyright 1995-96, Apple Computer, Inc.

Keywords: kppc, kpbook, specsht, 5300

\_\_\_\_\_

This information is from the Apple Technical Information Library.

19960804 13:39:46.00

Tech Info Library Article Number: 18434