



Tech Info Library

Performa 475 & 476: Specifications (8/95)

Article Created: 1 October 1993

Article Reviewed/Updated: 15 August 1995

TOPIC -----

This article provides the technical specifications for the Macintosh Performa 475 and Performa 476 computer systems. These two products differ in three ways:

- Hard drive capacity
- Application software installed
- Where sold

DISCUSSION -----

Microprocessor

- 68LC040, 32-bit architecture, 25 MHz clock frequency
- CMOS custom clock/calendar with long-life lithium battery

Memory

4MB RAM, expandable to 36MB
512K VRAM for 256 colors, expandable to 1MB for 32,000 colors

Display

- Macintosh Performa Plus Display (14 inch)

with 512K of VRAM:
640 x 480 pixels with 1, 2, 4, or 8 bits per pixel
(256 colors/grays)

with 1MB of VRAM:
640 by 480 pixels with 1, 2, 4, 8, or 16 bits per pixel
(thousands of colors/256 grays)

Storage

- Built-in Apple SuperDrive 1.4MB high-density floppy disk drive, reads disks from Macintosh, Apple II, MS-DOS, and Windows systems
- Performa 475: internal 160MB SCSI hard disk drive
- Performa 476: internal 230MB SCSI hard disk drive

- Optional external SCSI hard disk drives (several capacities available)
- Optional external AppleCD CD-ROM drive

Modem

- TelePort/Bronze for Macintosh Performa (from Global Village Communication, Inc.)
- GlobalFax software (send-only fax) for 9600-baud faxing from any application to fax machines worldwide (upgradable to receive fax via software)
- Modem also serves as 300/1200/2400-baud data modem
- No separate power adapter required

Power Input

- Line voltage: 90 to 240 volts AC, RMS single-phase
- Frequency: 50 to 60 Hz
- Power: 30 watts maximum, not including display power

Interfaces

- One Apple Desktop Bus (ADB) port supports a keyboard, mouse, and other devices (up to three devices) daisy-chained through a low-speed, synchronous serial bus
- Two serial (RS-232/RS-422) ports, 230 kilobits per second maximum (up to 920 Kbits per second if clocked externally)
- SCSI interface for connecting up to six external devices
- Video port supports shadowmask, RGB, and monochrome displays of various sizes and resolutions
- Sound output port (stereo) for external audio amplifier or headphones
- Sound input port for monaural sound input* (monaural 8-bit sound, sampled at 22 or 11 kHz)
- Internal PDS expansion slot for one expansion card

*NOTE:

The Apple PlainTalk Microphone, which is sold as a standalone product, is compatible with these systems. These products cannot use the older style low-level output microphone used on previous Macintosh models.

Keyboard and Mouse

- Apple Desktop Bus (ADB) keyboard with numeric keypad and two-level tilt adjustment
- Apple ADB Mouse II

Apple Desktop Bus Power Requirements

- Maximum current draw for all ADB devices: 200 milliamperes (mA)
- Recommended maximum of three ADB devices
- Mouse draws 10 mA
- Standard keyboard draws 25 mA (third-party keyboards draw up to 80 mA)

Sound Generator

-
- Stereo 8-bit sound that can drive stereo headphones or other stereo equipment through the sound jack.

Software

-
- Macintosh System Software version 7.1P3, designed specifically for Performa computers.
 - At Ease software lets adults share the computer with children -- while protecting valuable data.
 - Macintosh PC Exchange lets you work with MS-DOS and Windows disks.
 - Application software: a selection of productivity and communication tools already installed on the hard drive.
 - Launcher software provides easy way to launch applications, and provides easy access to service and support information, user tips, etc.

Disability Access

-
- CloseView, Easy Access, and "visible beep" software are built in.
 - Third-party options provide other alternative input and output devices

Size and Weight

-
- Main Unit
Weight: 8.8 lb. (4.0 kg)
Height: 3.2 inches (81 mm)
Width: 12.2 inches (310 mm)
Depth: 15.0 inches (382 mm)
 - Mouse
Weight: 4 oz. (0.10 kg)
Height: 1.3 inches (33 mm)
Width: 2.4 inches (61.7 mm)
Depth: 4.2 inches (107.3 mm)
 - Keyboard
Weight: 2.2 lb. (1 kg)
Height: 1.8 inches (44 mm)
Width: 16.5 inches (418 mm)
Depth: 5.6 inches (142 mm)

Environment

-
- Operating temperature: 10 to 40° C (50 to 104° F)
 - Storage temperature: -40 to 47° C (-40 to 116.6° F)
 - Relative humidity: 20% to 80% (noncondensing)
 - Maximum altitude: 3048 m (10,000 ft.)

Service and Support

-
- One year limited warranty
 - One year free in-home service
 - Toll-free help line
 - Support for non-Apple software is provided by the respective software publishers.

Article Change History:

- 15 Aug 1995 - Included PlainTalk microphone information.
- 26 Jul 1994 - Expanded sound output information.
- 24 Feb 1994 - Corrected ADB amperage rating

Support Information Services

Copyright 1993-95, Apple Computer, Inc.

Keywords: SPECSHT

=====

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 13580