

## Macintosh Performa 640 DOS Compatible: Specifications (7/95)

Article Created: 27 June 1995 Article Reviewed/Updated: 14 July 1995
TOPIC
This article provides the specifications of the Macintosh Performa 640CD DOS Compatible computer.
DISCUSSION
Common Features =========== Integration
<ul> <li>Run Mac OS and DOS or Windows software simultaneously <ul> <li>applications, games and CD-ROM titles</li> </ul> </li> <li>Toggle between operating systems with a keystroke <ul> <li>single monitor supports both</li> </ul> </li> <li>Copy &amp; paste between OS environments</li> <li>Easily share files and folders</li> <li>Use Mac compatible printer and peripherals with both operating systems</li> <li>Supports Apple monitors (High Resolution RGB up to Multiple Scan 15) or VGA and SVGA monitors</li> </ul>
Storage
<ul> <li>1.4 MB Apple SuperDrive floppy <ul> <li>Read and write Mac OS, MS-DOS, OS/2 and ProDOS disks</li> </ul> </li> <li>500 MB IDE hard drive, 1/3 height <ul> <li>PC files reside in virtual drive container</li> </ul> </li> <li>Double-speed CD-ROM drive</li> </ul>
Options
<ul> <li>CommSlot Ethernet card</li> <li>10 BASE-T, thin, thick, AAUI</li> <li>Apple Presentation System</li> </ul>
Bundled Hardware
• Apple Multiple Scan 15 Display

• AppleDesign Keyboard

• Global Village TelePort Gold 14.4Kps Fax Modem

```
Environment
_____
• Operating Temperature
  - 50° F to 104° F (10° C to 40° C)
• Storage Temperature
  - -40° F to 116.6° F (-40° C to 47° C)
• Relative Humidity
  - Operating: 10% RH to 90% noncondensing
  - Non-operating: 5% RH to 95% noncondensing
• Altitude
  - Operating: -1,000 to 10,000 feet
  - Non-operating: -1,000 to 40,000 feet
Weight
____
• 19 Pounds (8.6 Kg)
Dimensions
_____
• 12.6" X 16.5" X 4.3" (320 mm X 419 mm X 109 mm)
Electrical Requirements
_____
• Line voltage: 100-240 volts AC, RMS, single-phase, nominal
• Frequency: 50-60 hertz (Hz)
• Power consumption: 45 watts maximum, not including monitor
ADB Power Requirements
_____
• Maximum current draw for all ADB devices is 500 milliamperes (mA) (a maximum
of three Apple Desktop Bus devices is recommended)
• Mouse draws up to 10 mA
• Keyboard draws 25-80 mA (varies with model).
Other
____
• Front headphone jack
• Front controls for volume
• Infrared remote control
• Power on/off from keyboard
Macintosh Features
_____
Processor & RAM
_____
• 68LC040 running at 66/33 MHz
• 8 MB RAM standard
  - 4 MB on logic board, 4 MB in SIMM
  - Expandable up to 52 MB (32 MB in one SIMM, 16 MB in other)
  - Two 72-pin SIMM sockets
  - Expand single SIMM at a time
```

```
- 80 ns or faster
• 1 MB ROM
Expansion & Ports
_____
• Video-in slot (Optional)
• TV tuner slot (Optional)
• Communications slot
• SCSI, two serial, ADB, sound-in, sound-out
• Internal LC-Compatible 68030 processor-direct slot (PDS) with installed
DOS-Compatibility Card*
Video
____
• 1 MB DRAM video frame buffer
• 16-bit color at 640x480, 8-bit color at 800x600, 832x624
• Supports video in a window with optional card
Sound
____
• 8-bit monophonic sound input
• 8-bit stereophonic sound output (16-bit CD stereophonic playback)
· Sound input port for optional microphone or line input
• Two sound output ports, level nominally 0.5 volts RMS into 39 ohms
• Internal speaker, muted whenever a plug is inserted into either sound output
port
Software
========
System software
_____
• Mac OS System 7.5.1 with Apple Guide, AppleScript, PC Exchange
• At Ease
Third-party software bundles
-----

    American Heritage Dictionary

    ClarisWorks

                                      • MacLink Plus/Easy Open Translators
• Quicken
• Click Art Performa Collection
                                      • MacGallery Clip Art Treasure Pak
• Expresso
                                      • Zip Zap
• TelePort Gold II for Performa
                                     • TelePort Modem Legend Tour
                                      • eWorld Tour
• eWorld
CD bundles
_____
• TIME Almanac Reference Edition

    CardShop/StickerShop Plus

• 3D Atlas
                                      • 1995 Groiler's MM Encyclopedia
• Club KidSoft
DOS/Windows Features
_____
Processor & RAM
```

\_\_\_\_\_

```
• 486 DX/2 running at 66 MHz
• 4 MB RAM standard on SIMM
  - Expand up to 32 MB
  - One 72-pin SIMM socket
  - 80 ns or faster
• DMA for shared-memory support provided through Mac OS system software
Networking
_____
• Included ODI driver supports Novell NetWare IPX and TCP/IP protocols
Sound
____
• SoundBlaster 16 compatible audio out
Ports
____
• Joystick (DB-15)
• Serial ports emulate PC serial interface (COM1, COM2)
• Printer port emulates parallel port (LPT1) supporting PostScript, Epson and HP
PCL-style printer drivers
Video
• 512K DRAM video frame buffer
• 8-bit color at 640x480
  - 4-bit color at 800x600
• Supports VGA, SVGA, EGA, CGA standards
Software
_____
• DOS 6.22 and Windows 3.1 included
• SoundBlaster
*Note: The Macintosh Performa 640CD DOS Compatible computer is not upgradeable
to a PowerPC processor. The DOS Compatibility Card is installed in the single
PDS slot.
Article Change History:
14 Jul 1995 - Changed access
13 Jul 1995 - Clarified bundle information
06 Jul 1995 - Added specsht keyword.
Support Information Services
Copyright 1995, Apple Computer, Inc.
Keywords: specsht
_____
This information is from the Apple Technical Information Library.
```

19960215 11:05:19.00

Tech Info Library Article Number: 18031