



Tech Info Library

QuickTime and HyperCard: Closing External Windows (7/92)

Article Created: 17 April 1992

Article Reviewed/Updated: 23 July 1992

TOPIC -----

Both the Palette XCMD and the Picture XCMD -- and now the Movie XCMD -- will send a message to the current card signaling that a window is closing. These messages are, respectively, `closePalette`, `closePicture`, and `closeMovie`.

The parameters sent with the message identify the window that is closing: The first parameter is the window's name and the second parameter is the window's ID (window IDs are new in HyperCard 2.1). The message is sent when the window closes, either via a click in a close box, or by executing a "close window" statement.

DISCUSSION -----

Stack designers can define a `closePalette`, `closePicture`, or `closeMovie` handler to take care of any cleaning up or updating when a window is closed.

One restriction: Don't try to close the window again within a `closePalette`, `closePicture`, or `closeMovie` handler. The script can STILL refer to the window, for example, getting (or even setting) the window's location. The script can also close other windows -- but HyperCard will crash if the script tries to close the window (e.g., `close window id (the param of 2)`)).

This article is adapted from the Claris Tech Info database.
Copyright 1993, Apple Computer, Inc.

Keywords: <None>

=====

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 14167