



# Tech Info Library

## HyperCard 2.2 New Feature: AppleScript Support (12/93)

Article Created: 13 December 1993

TOPIC -----

HyperCard 2.2 supports Open Scripting Architecture (OSA). This means you can write HyperCard scripts either in HyperTalk, or in any language defined by an external scripting system: AppleScript, for example.

DISCUSSION -----

If you write in AppleScript, you can have your stacks or standalone applications communicate with other scriptable applications such as FileMaker Pro 2.0 and Microsoft Excel 4.0.

Scripts can receive messages as well as send or pass messages to other scripts, regardless of the script's language. So a button script written in HyperTalk can send a message to a card script written in AppleScript, which can, in turn, pass the message to a background script written in UserTalk.

HyperCard 2.2 accommodates scripting components that don't support the optional OSA event handling interface. You can invoke scripts that belong to such components by sending them a run message:

```
send "run" to button 1 -- run an attached QuicKeys script
```

For AppleScript details, see the HyperCard AppleScript Reference stack.

Note: To take advantage of AppleScript code in your stack, the user must be running System 7.0 (or later) and have AppleScript 1.1 installed.

This article was adapted from the HyperCard 2.2 New Features stack.

Article Change History:

24 December 1993 - deleted reference to both Apple Events Manager requirement  
Copyright 1993, Apple Computer, Inc.

Keywords: <None>

=====

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 14206