

LaserWriter II: Cleaning Agents and Lubricants (11/94)

Article Created: 1 August 1991 Article Reviewed/Updated: 09 November 1994

* RESTRICTED: Apple Internal and Support Providers Only * Not For General Public Release

TOPIC -----

Do you have a list of cleaning agents and lubricants for the LaserWriter II printers?

DISCUSSION -----

From the LaserWriter II Service manual:

Material Name	Use	Purchase	Remarks
Alcohol	Cleaning: Glass, Rubber, External Covers 	Locally 	All are flammable. Use in well-ventilated area. Avoid breathing concentrated vapor.
MEK (Methyl ethyl ketone)	Cleaning: Metal, Oil, and Toner Stains 	Locally 	<pre>Very flammable. Do not use for cleaning the drum, molded-plastic parts, or corona wires. Use in well-ventilated area. Avoid contact with eyes and excessive contact with skin.</pre>
Heat-Resistant Grease	Apply to Drive Mechanism 	HITASOL MO 1385 	<pre>This grease has highly superior load resistance, heat resistance, and anti-friction property. Gray color grease, 30 wt. Heat-resistant to 300C.</pre>
Lubricating Oil	Bearings 	ISO VG 68 Oil, Mobil Vactra Oil	Equivalent oil may be used.

		No.2, Shell Tonna Oil T68	
Lubricating Oil	Cassette Pickup Roller Clutch Spring 	ISO VG 220 Oil, Mobil Vactra Oil No.4, Shell Tonno Oil T220	Equivalent oil may be used.
Cotton Flannel	Cleaning: Drum 	Locally 	Should be soft enough for cleaning the drum and should not produce lint.

Article Change History: 09 Nov 1994 - Reviewed for technical accuracy.

Support Information Services Copyright 1991-94, Apple Computer, Inc.

Keywords: hts

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 7973