



Tech Info Library

System 7.x and Novell UAM Problems (4/93)

Article Created: 12 April 1993

* RESTRICTED: Apple Internal and Support Providers Only *
Not For General Public Release

TOPIC -----

I'm experiencing a weird problem with my Novell Netware server. It seems Netware and System 7.0 aliasing have a problem. If I'm on a network attached to a Novell server (3.11 with Mac NLM installed), make an alias of an application on the server and disconnect without the server window open, the alias won't open the application. I receive a message telling me the alias can't find the application. However, if the server window is open and I use the alias, it finds the application. I'm on a Macintosh running System 7.0. Macintosh type doesn't seem to matter in this instance. Has this ever been reported as a problem?

DISCUSSION -----

We believe you're using the special Novell UAM (User Authentication Method). If so, there is a known problem with symptoms nearly identical to those you reported when using the Novell UAM. The Alias Manager cannot mount volumes that need the Novell UAM.

Unfortunately, Apple has never supported alternate UAMs. This means Apple engineering does not consider the alternate UAM mechanism part of any current project, so there is no project to submit bugs against.

If you allow standard Apple UAM access to your Novell host, then the alias will work as expected.

Copyright 1993, Apple Computer, Inc.

Keywords: <None>

=====

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 11963