



# Tech Info Library

## AppleDesign Powered Speakers II: Specifications (8/96)

Article Created: 25 October 1994

Article Reviewed/Updated: 2 August 1996

TOPIC -----

This article contains the technical specifications of the AppleDesign Powered Speakers II.

DISCUSSION -----

### Speaker Type

-----

- Full-range, tuned-port, bass-reflex system

### Output

-----

- Maximum sound-pressure level (SPL) 90 dB at 0.5 m at 200 Hz
- Frequency Range: 150 Hz to 20 kHz
- Power 14 W

### Maximum Input Voltage

-----

- 2 volts peak-to-peak

### Interfaces

-----

- One stereo computer-sound input port
- One stereo CD/audio input port
- One stereo headphone output port

### Control

-----

- Volume on front panel

### Power Supply Output

-----

- 12 volts DC

### Electrical Requirements

-----

- Line voltage: 100 to 240 volts, depending on the power-supply module
- Frequency: 50 or 60 Hz

- Power: 24 W (maximum)

#### Size and Weight

- Height: 6.8 in. (175 mm)
- Width: 4.13 in. (107 mm)
- Depth: 3.94 in. (101 mm)
- Weight: 1.34 lb. (612 g)

#### System Requirements

- Any Apple Macintosh, Macintosh Performa, PowerBook, Power Macintosh, or Windows-based personal computer; CD or cassette player; or television that supports sound output.

#### Ordering Information

##### M3261LL/A

- Main (powered) speaker with amplifier and satellite speaker in slate color
- Power-supply module (120-volt input)
- Computer cable (with 3.5-mm miniplugs)
- CD stereo cable (3.5-mm miniplug to dual RCA jacks)
- Attached, insulated, dual-strand speaker-to-speaker cable with miniplug connectors
- User's guide
- Limited warranty

##### M2668LL/A

- Identical to M3261LL/A, but platinum in color to match Macintosh computers

#### Article Change History:

- 02 Aug 1996 - Article Reviewed.
- 03 Jan 1995 - Article reviewed.

Copyright 1994-96, Apple Computer, Inc

Keywords: specsht

=====  
This information is from the Apple Technical Information Library.

19960804 13:39:46.00

Tech Info Library Article Number: 16600