



Tech Info Library

Apple II 3.5 Disk Controller Card: Specifications (2/97)

Apple II 3.5 Disk Controller Card: Specifications (2/97)

Article Created: 11 December 1991

Article Reviewed/Updated: 12 February 1997

TOPIC -----

This article gives technical specifications for the Apple II 3.5 Disk Controller Card. This card has been discontinued by Apple.

DISCUSSION -----

Overview

The Apple II 3.5 Disk Controller Card allows you to use the 3.5-inch floppy disk drives, including the Apple SuperDrive and Apple 3.5 Drive, with an Apple IIGS or Apple IIe computer. The card also supports the operation of older model Apple II UniDisk 3.5 drives with the Apple IIe computer. This card replaces the UniDisk 3.5-inch Controller Card.

Drives Supported

Apple SuperDrive

Apple 3.5 Drive

Apple UniDisk 3.5 Drive (Apple IIe only)

Specifications

Microprocessor: 65C02

Disk controller: SWIM

Memory: 32K SRAM 32K ROM

Connector: DB-19

Power: Less than 4 watts

Environmental Requirements

Operating temperature: 50 to 104 degrees F (10 to 40 degrees C)

Storage temperature: 50 to 140 degrees F (10 to 60 degrees C)

Relative humidity: 20% to 80% noncondensing

Article Change History:

12 Feb 1997 - Reviewed for technical accuracy, revised formatting.

Copyright 1991-97, Apple Computer, Inc.

Keywords: SPECSHT

=====
This information is from the Apple Technical Information Library.

ArticleID: TECHINFO-0009292

19970213 10:18:12.00

Tech Info Library Article Number: 9292