



Tech Info Library

Macintosh: Order Of Devices Checked During Startup

Article Created: 24 April 1989

Article Change History

09/28/92 - REVIEWED

- For technical accuracy.

TOPIC -----

What is the order of devices checked by the Macintosh during startup?

DISCUSSION -----

Here is the correct order of devices the Macintosh checks during the startup sequence:

- 1) Floppy drive 0
 - On a Macintosh II, IIx, & IIfx this is the right-side internal drive.
 - On a Macintosh SE with two floppy drives, this is the lower drive.
 - On other systems, this is the internal drive.
- 2) Floppy drive 1
 - On a Macintosh II, IIx, & IIfx this is the left-side internal drive.
 - On a Macintosh SE with two floppy drives, this is the upper drive.
 - On other systems, this is the external drive.
- 3) Floppy drive 2
 - This applies only to a Macintosh SE with a third floppy drive.
- 4) Startup device selected via the Startup Disk CDEV
 - This may include SCSI or NuBus startup devices.
- 5) SCSI devices, beginning with ID 6 and ending with ID 0.
- 6) NuBus startup devices.
 - This applies only to a Macintosh II.

Both the "Inside Macintosh V" and the "Macintosh Family Hardware Reference" manuals state that the internal SCSI device is checked before

any other SCSI device, regardless of SCSI ID. This is NOT True. Unless the internal SCSI device is selected as the startup device via the Startup Device CDEV, it has no special priority during the startup process.
Copyright 1989 Apple Computer, Inc.

Keywords: <None>

=====

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 3873