Tech Info Library

LaserWriter Select 310: Pinouts (2/93)

Article Created: 9 February 1993

TOPIC -----

This article provides the pinouts for the LaserWriter Select 310's communications ports.

DISCUSSION -----

Mini DIN-8 RS-232 Serial Communications Ports

Signal	Description
DTR	Data Terminal Ready (output)
DSR	Data Set Ready (input)
TxD-	Transmitted Data
SG	Signal Ground
RxD-	Received Data
SG	Single Ground
NC	No Connection
NC	No Connection
PG	Protective Ground
	DTR DSR TxD- SG RxD- SG NC NC

Centronics Parallel Communications Port

Pin	Signal	Pin	Signal
1	Data Strobe	19	Ground
2	Data 0	20	Ground
3	Data 1	21	Ground
4	Data 2	22	Ground
5	Data 3	23	Ground
6	Data 4	24	Ground
7	Data 5	25	Ground
8	Data 6	26	Ground
9	Data 7	27	Ground
10	Acknowledge	28	Ground
11	Busy	29	Ground
12	Paper Out	30	Ground
13	(Select Printer)	31	No Connection

14	No Connection	32	(Printer error)
15	No Connection	33	No Connection
16	No Connection	34	No Connection
17	Signal Ground	35	No Connection
18	No Connection	36	No Connection
Copyr	ight 1993, Apple	Computer,	Inc.

Keywords: <None>

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 11520