



# Tech Info Library

## LaserWriter Select 360: Specifications (7/95)

Article Created: 1 October 1993

Article Reviewed/Updated: 25 July 1995

Topic -----

This article provides the technical specifications for the LaserWriter Select 360.

Discussion -----

Marking Engine

-----

Fuji Xerox laser-xerographic

Print Quality

-----

- PostScript: 300 or 600 dots per inch, selectable
- LaserJet III Emulation: 300 or 600 dots per inch

Printer Memory

-----

7 MB of RAM Standard, upgradable to 16 MB

Printer Fonts

-----

64 Fonts Are Provided, Including Such Fonts As ITC Avant Garde, ITC Bookman, Chicago, Courier, Delphian, Garamond Condensed, Geneva, Helvetica, Helvetica Black, Helvetica Narrow, Lubalin Graph, Lucinda Bright, Machine, Monaco, Nadianne, New Century Schoolbook, New York, Old English Text, Onyx, Oxford, Palatino, Swing, Symbol, Times, ITC Zapf Chancery, ITC Zapf Dingbats, And Zeal.

Laser

-----

- Type: semiconductor laser
- Wavelength: 780 nanometers
- Output Power: 5 milliwatts maximum

Speed

-----

Ten pages per minute maximum. Actual speed depends on the images printed and the computer used.

## Interfaces

-----

- One LocalTalk port
- One Parallel (36-pin Centronics) port
- One RS-232 serial port

## Recommended Duty Cycle

-----

Minimum life expectancy is 300,000 pages, with no monthly page limit.

## Paper Feed

-----

Automatic feed from paper cassettes and multipurpose tray; manual feed for single sheets

## Energy Star

-----

The LaserWriter Select 360 is EPA Energy Star-compliant

## Printing Materials

-----

Apple recommends 20-lb. photocopy or typewriter bond. You can use 16-lb. to 28-lb. paper in the cassette trays, and 16-lb. to 36-lb. paper via manual feed. The printer accepts most letterhead and colored stock, and medium-weight photocopier transparencies. Print labels or transparencies using manual feed or the multipurpose tray. Use envelopes recommended for Laser printers. Print envelopes using manual feed or automatically if you have the optional envelope cassette installed. Paper made with talc is not recommended for use with this printer.

## Paper Capacity

-----

- Standard Cassette: Holds up to 250 sheets of U.S. Letter, A4, or B5 paper Sizes.
- Optional Cassettes are available for 250 sheets of U.S. legal paper and 500 sheets of U.S. Letter or A4 paper.
- Multipurpose Tray: Holds up to 50 sheets of U.S. legal, A4, U.S. letter B5, or executive paper, or 5 envelopes.
- Envelope Cassette: Holds up to 30 Com-10, Monarch, D1, or C5 envelopes.

## Imageable Area

-----

- Maximum printable line: 8.1 inches (207.7 mm)
- Minimum top, left and right margins: .194 inches (4.9 mm)
- Minimum bottom margin: .167 inches (4.2 mm)

Actual imageable area may vary depending on the application program. The printer senses cassette size and adjusts to maintain these margins.

## Paper Sizes

-----  
Width: Minimum - 97mm (3.82 in) Maximum - 216mm (8.5 in)  
Length: Minimum - 148mm (5.83 in) Maximum - 356mm (14.0 in)

#### Dimensions

-----  
Height: 8.0 inches (25.8 Cm)  
Width: 15 inches (38 Cm)  
Depth: 18.3 inches (45.8 Cm)

#### Weight

-----  
29 pounds (13.2 Kg)

#### Acoustic noise levels (bystander position)

-----  
Standby: 36dBA  
Printing: 47 dBA

#### Operating Environment

##### Humidity

-----  
20 To 80 percent, noncondensing

##### Toner cartridge transit environment

-----  
-4 to 104 deg. F (-20 to +40 deg. C)

##### Input Electrical Requirements

-----  
U.S./Japan: 100-115 V (+/- 10%), 50-60 Hz (+/-2 Hz)  
Europe/Australia: 220-240 V (+/-10%), 50 Hz (+/-2 Hz)

##### Power Consumption

-----  
Operating: 450 W maximum at 115 V or 220 V

##### Ozone Emission

-----  
0.05 parts per million maximum, measured in accordance with ECMA 129 of UL114 standards for ozone measurement

##### System Requirements

###### Macintosh:

-----  
System software 7 or later  
- Minimum 2 MB of memory (4 MB recommended)

###### System software 6.0.7 or 6.0.8

- Minimum 2 MB of memory

MS-DOS/Windows:  
Windows 3.0 or later  
- Minimum 2 MB of memory (4 MB recommended)

Ordering Information  
=====

LaserWriter 360 & accessory kit: M2049LL/A

LaserWriter 360 Bundle (printer, accessory kit & toner cartridge): B1333LL/B

LaserWriter Select Toner cartridge: M1960G/A

LaserWriter 360 PostScript Fax Card: M2345LL/A

LaserWriter Select 250-Sheet Feeder/Cassette: M2041G/A  
. (supports A4, U.S. letter, A5, and executive paper sizes)

LaserWriter Select 500-Sheet Feeder/Cassette: M2042G/A  
. (supports A4 and U.S. letter paper sizes)

LaserWriter Select 250-Sheet Letter Cassette: M2034G/A

LaserWriter Select Envelope Cassette (holds 30 envelopes): M2031G/A

LaserWriter Select Legal Cassette (holds 250 sheets): M2032G/A

Article Change History:

- 25 Jul 1995 - Revised maximum paper weights
- 20 Mar 1995 - Added paper sizes
- 13 Mar 1995 - Added System software requirements.

Support Information Services  
Copyright 1993-95, Apple Computer, Inc.

Keywords: specsht

=====  
This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 13706