



# Tech Info Library

## Personal LaserWriter: Specifications (Discontinued)

This article last reviewed: 20 July 1990

TOPIC -----

These are the technical specifications for the Personal LaserWriter.

DISCUSSION -----

### Printing Method

-----

Electrophotography (single-component dry toner)

### Printing Speed

-----

4 pages/minute

### Page Size Limits

-----

Width: min. 97 mm (3.2 in.)  
max. 216 mm (8.5 in.)  
Length: min. 148 mm (5.83 in.)  
max. 356 mm (14.01 in.)

### Paper

-----

Face Down Output: 16 to 24 lbs. single sheet photocopy bond  
Face Up Output: 16 to 28 lbs. letterhead and colored stock  
Standard Weight transparency material  
Envelopes and labels

### Paper Cassettes

-----

Multi-Purpose Tray: 50 sheets of 80 gr/sq m  
or 15 envelopes of 80 gr/sq m  
US Letter, US Legal, A4, B5, Envelope  
Manual: Single sheets: US Letter, US Legal, A4, B5, Envelope

### Print Delivery/Capacity

-----

Face down: 50 sheets  
Face up: 50 sheets

Service

-----

Duty cycle (month): no limit  
Minimum life expectancy: 150,000 pages  
Service interval: 100,000 pages  
Pages per Toner: 2500 pages

Noise

-----

Printing: under 54 dB(A) Max.  
Standby: under 40 dB(A) Max.

Weight & Dimensions

-----

width 15 inches, depth 18.3 inches, height 9.8 inches  
weight 32 lbs.

Power Consumption

-----

operating: maximum 600W (115V)  
550W (220V)

Line Voltage Requirements

-----

	Voltage (V) 10%	Frequency (Hz)
US/Japan	100/115	50/60
Europe/Australia	220/240	50

Copyright 1990 Apple Computer, Inc.

Keywords: SPECSHT

=====

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 5951