



Tech Info Library

Portable StyleWriter: Pinouts (6/93)

Article Created: 28 June 1993

TOPIC -----

This article lists the pinouts for the Portable StyleWriter's parallel connector and the Mini Din-8 Serial connector for the Macintosh.

DISCUSSION -----

Parallel connector (Printer)

Pin	Description	Pin	Description
1	Data Strobe	19	Ground
2	Data 1	20	Ground
3	Data 2	21	Ground
4	Data 3	22	Ground
5	Data 4	23	Ground
6	Data 5	24	Ground
7	Data 6	25	Ground
8	Data 7	26	Ground
9	Data 8	27	Ground
10	Acknowledge	28	Ground
11	Busy	29	Ground
12	Paper Out	30	Ground
13	(Select Printer)	31	(Input Prime)
14	Signal Ground	32	(Printer reset)
15	(OscExt)	33	ID7
16	Signal Ground	34	(Fault)
17	Shield	35	Ground
18	(+5V)	36	(Line Count)

Mini DIN-8 Serial Connector (Macintosh)

Pin	Signal	Description
1	CLK	Rxd and Txd clock (output)
2	NC	No Connection

3	TxD--	Transmitted Data (output)
4	SG	Signal Ground
5	RxD--	Received Data (input)
6	TxD+	Balanced transmit (output)
7	Vcc	+5 VDC regulated, 300 mA max (output power)
8	RxD+	Balanced receive (input)
Shield	PG	Protective Ground

Copyright 1993, Apple Computer, Inc

Keywords: <None>

=====

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 12456